

130MM Large Strobe

FEATURES

- High intensity Xenon Flash
- Polycarbonate, double-cut prism lens
- 500 mm (19.6 in.) PVC jacketed leads
- Transient voltage and reverse polarity protection
- Dual-voltage (10-32 VDC), 110 and 220 AC models
- IP65 rated (weatherproof), gasket included
- All models are CE compliant
- 1 year warranty



COMPLETE ASSEMBLY

Model Type: SL-RB

Voltage: 4XDV (10-32VDC), 2X110 (110VAC), 2X220 (220VAC)

Color: Red (-R), Amber (-Y), Green (-G), Blue (-B), Clear (-C)

Ordering Example: SL-RB2X110-R (Large Strobe, 110 VAC, Red)

OPTIONAL COMPONENTS

- Single bolt mounting kit (FX7)
- Metal wire guard (FX9)
- Pole mount base (FX13)
- Wall mounting bracket (FX14)
- Surface mount base (FX28)
- Magnet mount with 12 VDC plug (FX60)
- Rechargeable battery powered beacon
- Rechargeable battery powered beacon long life
- 2, 5, 6, 10 and 15 watt units available
- Multi-voltage (10-100 VDC, 20-72 VAC)

VOLTAGE	CURRENT	FLASH/MIN
110V AC	19 ma	130
220V AC	46 ma	130
12V DC	600 ma	75
24V DC	300 ma	75



FX7



FX9



FX13



FX28



FX60



BATTERY

DIMENSIONS

