

## 93mm Surface Mount Sealed Strobe

### FEATURES

- 28 adjustable tones with volume up to 116 db at 1 meter  
 2 tones from one alarm with NPN connection
- 2 base depths:
  - Short base – 76 mm tall IP54 panel mount
  - Tall base – 103 mm tall IP65 with PG16 entry
- Acoustical frequency range for the 26 tones is .4 to 3.0 KHz
- Temperature range is -40 C to 80 C
- White ABS Plastic
- IP54 with short base or IP65 with tall, surface-mount base
- CE approved (SEE must use tall base for CE approval)



### COMPLETE ASSEMBLY

#### MODEL TYPE:

- **SEP** Audible Alarm, DC
- **SEE** Audible Alarm, AC
- **SEPS** Audible Alarm with Strobe, DC

**VOLTAGE:** 024: 9-28 VDC, 240:110-240 VAC 50/60 Hz

**COLOR (for strobe on SEPS only):** Red, Amber, Blue, Green, Clear

**BASE:**26: Short Base 76: Tall Base (surface mount)

- Red color body available

**ORDERING EXAMPLE:** SEP-024-26 Panel buzzer, short base, DC

MODEL	CURRENT- 24	CURRENT- 24
SEP	8 mA	12 mA
SEPS	110 mA	68 mA
SEE	35mA at 240 VAC	



### DIMENSIONS

